



www.tankcontainer.com

T-CODES				
T-CODE	MIN TEST PRESSURE	MIN SHELL THICKNESS ⁺	PRESSURE RELIEF VALVE	BOTTOM OUTLET CLOSURES
T1	1.5	6 mm*	Normal	2
T2	1.5	6 mm*	Normal	3
T3	2.65	6 mm*	Normal	2
T4	2.65	6 mm*	Normal	3
T5	2.65	6 mm*	SRV w/ rupture disc	PROHIBITED
T6	4	6 mm*	Normal	2
T7	4	6 mm*	Normal	3
T8	4	6 mm*	Normal	PROHIBITED
T9	4	6 mm	Normal	PROHIBITED
T10	4	6 mm	SRV w/ rupture disc	PROHIBITED
T11	6	6 mm*	Normal	3
T12	6	6 mm*	SRV w/ rupture disc	3
T13	6	6 mm	Normal	PROHIBITED
T14	6	6 mm	SRV w/ rupture disc	PROHIBITED
T15	10	6 mm*	Normal	3
T16	10	6 mm*	SRV w/ rupture disc	3
T17	10	6 mm	Normal	3
T18	10	6 mm	SRV w/ rupture disc	3
T19	10	6 mm	SRV w/ rupture disc	PROHIBITED
T20	10	8 mm	SRV w/ rupture disc	PROHIBITED
T21	10	10 mm	Normal	PROHIBITED
T22	10	10 mm	SRV w/ rupture disc	PROHIBITED
T-50	11	178.276	178.276 (e) (3)	3
<i>For transport of non-refrigerated gases</i>				
T-75	3	178.277 (b)	178.277 (e)	3
<i>For transport of refrigerated gases</i>				

+ in reference steel

*5 mm if diameter < 1.8m